

Lubricating Fluid

Type R OS2:

A low viscosity odourless oil-based fluid for use where water is not permitted.

Type GW2:

A low viscosity water-based fluid specially developed for use with Kemet Diamond Suspension, particularly when used with Kemet Lapping Plates.

Type Blue:

Improves cutting and polishing performance. Can be used on polishing cloths or Kemet plates.

	Type R OS2	Type GW2	Type Blue
Size	Code	Code	Code
1 litre	301511	301105	301158
2.5 litres	301512	301108	301156
5 litres	301141	301107	301159
450ml (Trigger Spray)	301513	301514	301200



Aluminium Oxide Powder

For smoothing operations.

Aluminium Oxide Powder

Micron	Size	Code
3	5kg	361607
5	5kg	361618
9	5kg	361555
12.8	5kg	361510
17	5kg	361619
23	5kg	361554
29	5kg	361620

Polishing Alumina

For use on most materials in polishing stages.

Alumina Powder

Micron	Size	Code
Gamma 0.04	1kg	600251
Alpha 0.3	1kg	600252
Alpha 1.0	1kg	600253

Silicon Carbide Powder

For lapping of Petrographic Material. Available in six grit sizes.

Green Silicon Carbide Powder

Grit	Size	Code
180	5kg	361541
220	5kg	361531
320	5kg	361617
400	5kg	361512
600	5kg	361563
1000	5kg	361535

Miscellaneous Polishing Suspensions

Various polishing suspensions for use on special applications.

Description	Micron	Size	Code
Non Crystallising Col-K Colloidal Silica Suspension for use on most materials at polishing stage.	0.06	5 litres	600199
	0.06	20 litres	600202
Alumina Suspension No.1	0-1	1 litre	600711
Alumina Suspension No.2	0-0.7	1 litre	600712
Alumina Suspension No.3	0-0.3	1 litre	600713

